



RHP

平面大功率电阻器
FLAT BIG POWER RESISTOR

特点 FEATURES

- | | |
|--|--|
| <input type="checkbox"/> Big pulse power | 脉冲功率负荷高 |
| <input type="checkbox"/> Easy to mount with only a single screw | 极易安装只需一颗螺钉 |
| <input type="checkbox"/> Small size only 1.5 cm tall | 小体积只有 1.5cm 高 |
| <input type="checkbox"/> TCR as low as $\pm 25\text{ppm}/^\circ\text{C}$ | 最好温度系数可达 $\pm 25\text{ppm}/^\circ\text{C}$ |

**降功耗曲线 Derating-curve**

| | 功率 power | L | W |
|--------|----------|------|------|
| RHP- 1 | 100W | 51.5 | 40.5 |
| RHP- 2 | 200W | 61.5 | 51.5 |
| RHP- 3 | 300W | 69.5 | 61.5 |

功率和尺寸 Power and sizes**技术参数 Technical Data**

| 参数 parameters | RHP- 1 | RHP- 2 | RHP- 3 |
|--------------------------|---|-----------------------------------|--|
| Resistance values 阻值 | 4.7,10,33,47,68 100,150,200 Ω | 10,22,47,100 150 Ω | 1,2,5,10,12,22,47,68 100,125,150,180,200 Ω |
| Tolerance 精度 | 5% 10% | 5% 10% | 5% 10% |
| TCR 温度系数 | $\pm 25\text{ppm}/^\circ\text{C}$ | $\pm 25\text{ppm}/^\circ\text{C}$ | $\pm 25\text{ppm}/^\circ\text{C}$ |
| Temperature range 温度范围 | -50°C-150°C | -50°C-150°C | -50°C-150°C |
| Max. pulse power 最大脉冲功率 | 1KW | 2KW | 3KW |
| Thermal resistance 热阻 | <0.15°C/W | <0.1°C/W | <0.05°C/W |
| Operating voltage 最大工作电压 | 1000VAC | 1000VAC | 1000VAC |
| Dielectric voltage 绝缘电压 | 2500VAC | 2500VAC | 2500VAC |
| Stability 稳定度 | <1% 2000h | <1% 2000h | <1% 2000h |

Many more values are available. 其他阻值可协商供货

应用范围 Application

特别适用于制动电阻，应用于软启动电路以及一切需要大功率小体积的场合

Ideal for use as a dynamic braking resistor, in a soft-start motor circuit.