

RI80f

平面高阻高压电阻器

FLAT HIGH OHM AND VOLTAGE RESISTOR

Ranges/TC/ VCR/Toler.	1210	2512	4020	30	40	50
1M-100M	1/2/5/10%	0.5/././10%	0.25/././10%	0.25/././10%	0.25/././10%	0.25/././10%
	TC50/100	TC50/100	TC25/50/100	TC25/50/100	TC25/50/100	TC25/50/100
	<50ppm/V	<10ppm/V	<5ppm/V	<2ppm/V	<1ppm/V	<1ppm/V
>100M-1G	2/5/10/20%	1/.../20%	0.5/.../20%	1/.../20%	1/.../20%	1/.../20%
	TC100/250	TC50/100	TC25/50/100	TC50/100/250	TC50/100/250	TC25/50/100
	<100ppm/V	<25ppm/V	<10ppm/V	52ppm/V	<2ppm/V	<1ppm/V
>1G-10G	5/10/20%	2/.../20%	1/.../20%	5/.../30%	5/.../30%	5/.../30%
	TC250/500	TC100/250	TC50/100	TC250/500	TC250/500	TC100/250
	<500ppm/V	<100ppm/V	<25ppm/V	<20ppm/V	<10ppm/V	<5ppm/V
10/20/30%	5/.../30%	5/.../30%				
TC500/1000	TC250/500	TC100/250				
>10G-100G	<1000ppm/V	<250ppm/V	<100ppm/V	<20ppm/V	<10ppm/V	<5ppm/V
	5/.../50%	5/.../30%	5/.../30%			
	TC500/1000	TC250/500	TC500/1000			
>100G-1T	-	5/.../50%	5/.../30%	5/.../30%	5/.../30%	5/.../30%
	-	TC500/1000	TC250/500	TC500/1000	TC500/1000	TC250/500
	-	<500ppm/V	<250ppm/V	<100ppm/V	<50ppm/V	<25ppm/V
>1T-10T	-	-	-	-	-	10/20/30%
	-	-	-	-	-	TC500/1000
	-	-	-	-	-	<100ppm/V

温度系数测试范围 Temperature range : +25°C--+85°C

电压系数测试范围 VCR measured between 10V---100V

更高的精度，更好的温度系数、电压系数、不同的外形尺寸可协商供货

Best tolerance , TCR, VCR and other sizes could be available .

应用范围 APPLICATION

SML 公司 RI80f 系列产品特别适合于高压电源，高保真话筒，医疗电子，音响，烟雾探测，红外探测，辐射探测，各种气体探测等高压及小信号放大电路。

SML type RI80f are suited for high voltage power supply, audiophile speakers, medical electronical devices, audio systems, smoke sensors, infrared detectors, radiation detectors, special gas detectors etc. all the fields of high voltage and small signal multiply